



P/N: FAPE481690




Outline Dimensions(Unit:mm)



Front View



Side View



Bottom View



Top View

Note:


- 1.Remove Pins 2,5,7,9,10,12.

Wave Soldering



- Note:
- 1.Never Contact the ceramic with the iron tip;
 - 2.1.0mm tip diameter(max).

Electronical Schematic



Electrical Characteristics

Input 230Vac 50Hz to (1-6 short 3,4)
 or Input 115Vac 60Hz to (1,4-3,6):
 Excitation current(I_x):32mA Max.
 Output: V_o=12.0Vac Typ(No-load).
 V_L=9.0Vac±5%(@1111mA).
 Hi-Pot: Pri-Sec:4000VAC/5mA/60Second.

General Properties

Operating Temperature:-25°C to +40°C.
 Storage Temperature:-25°C to +85°C.
 Insulation Class: B.
 Weight: 0.30kg.

REV	DESCRIPTION	APPD	DATE	Tianchang Fuan Electronic Co Ltd www.fuantronics.net TEL: +86-550-7814888 FAX: +86-550-7831133	 Tolerances unless otherwise specified: (X)±0.50 (XX)±0.25 Unit of measurement: mm	Make: Qiumei.Liu Checked: Beson. zhan Approved: Anson. zhan	DRAWING TITLE 10.0W Encapsulated Transformer For EI48*16.8,2*115VAC Input 50/60Hz	Customer Name:
							Material Number: A224816XS250	Document/Rev: 00
								Specification Sheet: 1 of 2


P/N: FAPE481690



List of UL Certificate:

No.	Part Name	Mat'l Description	Supplier	UL Number
1	Bobbin	EI48*16.8/PBT(Black)	Chang Chun Plastics Co Ltd	E59481
2	Case	CASE-EI48*16.8/PA66(Red)	Zhejiang Juner New Materials Co Ltd	E204321
3	Copper wire	2UEW-F/155C	Elektrisola Hangzhou Co Ltd	E258243
4	Core	Lamination	Ta Yea Steel Industry Co Ltd	N/A
5	Epoxy	PU552(Black)	Wevo-Chemle Gmbh	E108835
6				



				Tianchang Fuan Electronic Co Ltd www.fuantronics.net TEL: +86-550-7814888 FAX: +86-550-7831133	 Tolerances unless otherwise specified: (.X)±0.50 (XX)±0.25 Unit of measurement: mm	Make: Qiumei.Liu Checked: Beson. zhan Approved: Anson. zhan	DRAWING TITLE 10.0W Encapsulated Transformer For EI48*16.8,2*115VAC Input 50/60Hz Material Number: A224816XS250	Customer Name: Document/Rev: 00 Specification Sheet: 2 of 2 Date of Recognition: Jan./02/2020
REV	DESCRIPTION	APPD	DATE					