



P3 **T18*10*8** **C/P**
Material **Core Size** **Coating**
 材质 品名 涂装

C=Epoxy. P=Parylene.

Ferrite core


Dimensions: (UNIT:mm)

Dimensions(mm)			Wt(g/set)
Epoxy Coating Dimensions(mm)			
ΦD1	ΦD2	H	6.55
18.0±0.40	10.0±0.30	8.0±0.30	
19.10max	9.10min	8.90max	



Test Conditions

AL: F=10.0KHz U=0.3V N=10Ts



Effective parameter

	Ve(mm3)	Ae(mm2)	Le(mm)
	1290	31.1	41.5

Coating

The core are coated with epoxy, flame retardant in accordance with "UL 94V-0" file number E228348.


The colour is green.

Ring core data


GRADE	AL(nH)	μi	TYPE NUMBER
P3	2300±25%	≈2300	T18/10/8/P3
H5K	4700±25%	≈5000	T18/10/8/H5K
H7K	6600±25%	≈7000	T18/10/8/H7K
H10K	9400±30%	≈10000	T18/10/8/H10K

Note:


- 1: Document is the property of FUAN Inc & is not allowed to be duplicated without authorization
- 2: RoHS compliant.




P3



H5K



H7K



H10K